

2MP AI Human Tracking Pan Tilt Zoom*4 Wifi Camera



FEATURES

- 3D AI human recognition and detection; automatic human tracking.
- Support dual light function, motion detection triggers on white light.
- H.265 compression format, low storage consumption.
- Support 4X optical ZOOM, support the whole synchronous focus.
- Starlight image sensor, the image is clearer.
- Support ONVIF connect to NVR equipment.
- Support 256 presets, easy to handle a variety of scenarios.
- Support AP hotspot function, easy realize equipment direct connection, off-line monitoring.
- Metal front face, suitable for a variety of application scenarios.
- External 5dBi wifi double antenna, stable information, harmonious and beautiful

appearance.

- Multi-platform management, APP/DVR/NVR/CMS/IE explorer.
- Built-in microphone, speaker, easy intercom.
- Remote video download and share.
- Support FTP transmission.
- Human detection alarm, motion detection alarm, speaker alarm.
- Support maximum 128GB TF card.
- Standard port function.

APPLICAION:

Warehouse, Underground parking lot, Bar, Hotels, Offices, Banks, Supermarkets





AirLink Ilife Inc

Networking | 4G IP Camera | Smart Home IOT

www.airlink-ilife.com sales@airlinkwifi.net

SPECIFICATIONS

Product	Model No.	AS-A02
	Type	2.4G Wifi Camera
	Lens	2.8mm-12mm
	Hemisphere rotation range	Level : 0-350° Vertical : 0-93°
	Horizontal rotation velocity	0-35°/s
	Vertical rotation velocity	0-25°/s
	Automatic rollover function	Not support
	White lights/infrared light	4 PCS white lights + 4 pcs infrared lights
	Number of presets	256 points
	Mechanical zero calibration	Support
	Human tracking	Support
System	Main processor	Hi3516EV200
	Operating system	Embedded LINUX operating system
Video	Image sensor	1/2.9 F37
	Video coding standard	H.265
	System standard	PAL/NTSC (APP selection)
	Effective resolution	1920*1080/1280*720/680*480
	Effective Pixels	2.4 MegaPixels
	Video frame rate	25fps
	Video stream	135kbps-2048kbps
	Signal to noise ratio	Signal to noise ratio ≥69dB
	Minimum illumination	Day mode 1Lux, night vision mode 0.01Lux
	Day and night mode	External control
	Backlight compensation (BLC)	AUTO
	Automatic white balance (AWB)	AUTO
	Automatic Electronic Shutter (AES)	AUTO/ 1/50 (1/60) -1/100,000sec
	Video output	AirLinkVMS 36Chanel client/mobile APP client
	Motion Detection	Stand by
	Capture function	Stand by
Audio	Coding standard	G.711U
	Audio input	Built-in onboard microphone MIC

	Audio output	External 8Ω/MAX 1.5W speaker
Video management	Video mode	Mobile video, alarm video, timed video, human video
	Video saving	TF card
Alarm	Alarm input/output	Not support
	Alarm trigger	Human alarm, motion detection alarm, speaker alarm, alarm video, capture, send email, alarm picture push
Internet	Network module	2* 2.4GHz Antenna
	Wifi protocol	Support for 802.11 b/g/n
	Wifi transmission distance	Straight line transmission 10m-30m (depending on WIFI signal)
Other	TF card capacity	Maximum support 128GB (common FAT32 format)
	Power consumption	≤ 8W
	Power	DC 12V2A

