

5MP AI Human Tracking Pan Tilt Zoom*18 PoE Camera



FEATURES

- 3D AI human recognition and detection; automatic human tracking.
- Support dual light function, motion detection triggers on white light.
- H.265 compression format, low storage consumption.
- Support 18X optical ZOOM, support the whole synchronous focus.
- Starlight image sensor, the image is clearer.
- Support ONVIF connect to NVR equipment.
- Support 256 presets, easy to handle a variety of scenarios.
- Support AP hotspot function, easy realize equipment direct connection, off-line monitoring.
- Metal tooling, suitable for a variety of application scenarios.
- Multi-platform management, APP/DVR/NVR/CMS/IE explorer.
- Built-in microphone, speaker, easy intercom.
- Remote video download and share.
- Support FTP transmission.
- Human detection alarm, motion detection alarm, speaker alarm.



AirLink ilife inc

Networking | 4G IP Camera | Smart Home IOT
www.airlink-ilife.com sales@airlinkwifi.net

- Support maximum 128GB TF card.
- Standard port function.

APPLICAION:

Warehouse, Underground parking lot, Bar, Hotels, Offices, Banks, Supermarkets



SPECIFICATIONS

Model No.	AS-A03
DSP	HI3516EV200
Sensor	Sony 335
Resolution	5MP: 2592*1944
Frame Rate	2592*1944 , 1-15(20)fps ; 2592*1520 , 1-22(30)fps 2304*1296 , 1-25(30)fps ; 1920*1080 , 1-25(30)fps
Lens	5.2mm-93.6mm
Power	12V3A
Operating Temperature	-40℃~+70℃



AirLink ilife inc

Networking | 4G IP Camera | Smart Home IOT

www.airlink-ilife.com sales@airlinkwifi.net

Consumption	≤15W
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°
Pan Rotation Speed	0-80°/s
Tilt Rotation Speed	0-45°/s
Tracking Effective Range	5M-45M
Tracking Speed Range	3-12KM/h
3D Tracking Region	A single point trigger / 1-16pcs multipoint trigger
Auto Flip	Horizontal 180°, Vertical 93°
Led	4pcs IR Led+4pcs Laser Led/8pcs Warm Light Led optional
Light Distance	About 120Meters
A-B Scan	User Programmable
Preset Points	256pcs
Guard Tours	3 groups(Max.16 points, dwell time user selectable)
Mechanical Zero Calibration	Support
Video Compression	H.265/H.264/ M-JPEG
Audio Compression	G711U
Voice Intercom	Built-in Two Way Audio
Mobile View	Support Android/Ios Smart Phone
APP	P6SLite
Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,PPPoE,P2P.
Software Control	IE, AirLinkVMS, Management Platform
Network Security	HTTPS,802.1X,IP ADDRESS FILTERING
Quick Command	PELCO Instruction Set
WaterProof	IP66
Lightning Protection	Transient voltage 6000V
Packing Case Size	1pc:18.5x18.5x28.5 6pcs:57.5x39.5x31
Weight	1pc:2.26kg 6pcs: 14.47kg



AirLink ilife inc

Networking | 4G IP Camera | Smart Home IOT

www.airlink-ilife.com sales@airlinkwifi.net

